

AFRMIR-SO-AL

Rack Mount Swing Out FDP



FEATURES

- Front Access Swing Out Panel
- For Indoor Rack Mount Applications
- Powder Coated 14 Gauge Aluminum (Beige or Black)
- Bulkhead Panel for up to 24 SC Simplex/LC Duplex Adapters (SC Footprint)
- Accommodates up to 24 Splices
- Integrated Cable Management
- Flush Mountable

The AFRMIR-SO-AL provides protection for fiber optic terminations and splices. The enclosure accommodates (2) LGX style adapter plates and can be configured to house up to (24) SC footprint adapters and 24 splices when equipped with splice trays. When installed, the swing out panel offers convenient front access to the terminations and splice trays and. The AFRMIR-SO-AL is available fully loaded as a patch only, patch and splice, or it can be equipped with a pre-terminated stub cable per the customer's specifications. The enclosure is configured for 19" racks as standard; 23" mounting brackets are available separately.

SPECIFICATIONS

Model	AFRMIR-SO-AL
Dimensions	1.75"h X 17"w X 11.5"d
Material	14 Gauge Aluminum
Maximum Termination Capacity	24 SC or 48 LC (Patch Only)
Splice tray Capacity When Equipped	24 Splices

ACCESSORIES

SC Simplex SM Adapter, Blue	AFAD2F2F
SC/APC Simplex SM Adapter, Green	AFAD5F5F
LC Duplex SM Adapter, Blue	AFAD4F4F-DU-SC
LC Duplex MM Adapter, Aqua	AFAD4F4F-DU-10G-SC
LC/APC Duplex SM Adapter, Green	AFAD4F4F-DU-SCI
SC Simplex MM Adapter, Beige	AFAD2F2F-MM
LC Duplex MM Adapter, Beige	AFAD4F4F-DU-MM-SC