

# AFWMS-2x2-OSP

## OSP Wall Mount FDP



\*Shown Loaded As 12 Port SC Patch and Splice.

### FEATURES

- For Outdoor Wall or Pole Mount Applications
- Powder Coated 11 Gauge Aluminum (Beige)
- Accommodates up to 24 Ports SC or 48 Ports LC
- Accommodates up to (2) splice trays
- (4) 7/8" Diameter Cable Entry Points
- NEMA 4 Rated

The AFWMS-2x2-OSP provides NEMA 4 protection for fiber terminations and splices in the outside plant environment. The enclosure is equipped with (4) 7/8" ports for cable entry and accommodates (2) LGX 118 adapter plates and up to (2) splice trays. The enclosure is configured for wall mounting but may also be pole mounted using the optional pole mounting hardware. The AFWMS-2x2-OSP is available as a patch only, patch and splice, or can be equipped with a pre-terminated stub cable per the customer's specifications.

### SPECIFICATIONS

Model	AFWMS-2x2-OSP
Dimensions	19"h X 10.3"w X 4.4"d
Material	11 Gauge Aluminum
Maximum Termination Capacity	(24) SC or (48) LC
Splice tray Capacity When Equipped	48 Splices

### ACCESSORIES

AFWMS-2X2-OSP Pole Mount Bracket	AFPM2X2
----------------------------------	---------