

# AFWMS-4X2

## Wall Mount FDP



### FEATURES

- For Indoor Wall Mount Applications
- Powder Coated 16 Gauge Cold Rolled Steel (Beige or Black)
- Accommodates up to 48 Splices
- Bulkhead Panel for 48 SC Simplex/LC Duplex Adapters (SC Footprint)
- 4 Entry Ports
- Integrated Cable Management
- Optional Keyed Lock Available

The AFWMS-4X2 provides protection for fiber optic terminations and splices. The enclosure is equipped with 4 ports for cable entry. The enclosure accommodates (4) LGX style adapter plates and can be configured to house up to (48) SC footprint adapters and 48 splices. The AFWMS-4X2 is available unloaded, with pigtailed and adapters, or can be equipped with a pre-terminated stub cable per the customers specifications.

### SPECIFICATIONS

Model	AFWMS-4X2
Dimensions	13" x 12" x 3"
Entry Points	4, 1.5" Diameter
Material	16 Gauge Cold Rolled Steel
Splice Holder	48 Splices

### ACCESSORIES

SC Simplex SM Adapter, Blue	AFAD2F2F
SC/APC Simplex SM Adapter, Green	AFAD5F5F
LC Duplex SM Adapter, Blue	AFAD4F4F-DU-SC
LC Duplex MM Adapter, Aqua	AFAD4F4F-DU-10G-SC
LC/APC Duplex SM Adapter, Green	AFAD4F4F-DU-SCI
SC Simplex MM Adapter, Beige	AFAD2F2F-MM
LC Duplex MM Adapter, Beige	AFAD4F4F-DU-MM-SC