

AFRM2R-6X3

Rack Mount FDP



*Shown Loaded As 48 Port SC/UPC Patch and Splice.

FEATURES

- For Indoor Rack Mount Applications
- Powder Coated 16 Gauge Cold Rolled Steel (Beige or Black)
- Accommodates up to 72 Splices
- Bulkhead Panel for up to 72 SC or 144 LC Ports (Patch Only)
- Removable Acrylic Front Door

The AFRM2R-6x3 provides protection for fiber optic terminations and splices. The enclosure is equipped with 4 ports for cable entry. The enclosure accommodates (6) LGX style adapter plates and can be configured to house up to (72) SC footprint adapters and (72) splices when equipped with splice trays. The AFRM2R-6x3 is available fully loaded as a patch only, patch and splice, or can be equipped with a pre-terminated stub cable per the customer's specifications. The enclosure is configured for 19" racks but reversible mounting brackets allow quick conversion for 23" racks.

SPECIFICATIONS

Model	AFRM2R-6x3
Dimensions	3.5"h X 17"w X 12"d
Material	16 Gauge Cold Rolled Steel
Maximum Termination Capacity	72 SC or 144 LC (Patch Only)
Splice tray Capacity When Equipped	72 Splices

ACCESSORIES

SC Simplex SM Adapter, Blue	AFAD2F2F
SC/APC Simplex SM Adapter, Green	AFAD5F5F
LC Duplex SM Adapter, Blue	AFAD4F4F-DU-SC
LC Duplex MM Adapter, Aqua	AFAD4F4F-DU-10G-SC
LC/APC Duplex SM Adapter, Green	AFAD4F4F-DU-SCI
SC Simplex MM Adapter, Beige	AFAD2F2F-MM
LC Duplex MM Adapter, Beige	AFAD4F4F-DU-MM-SC