

# AFWMC-I

## Wall Mount FDP



\*Shown Loaded As 12 Port SC/APC Patch Only

### FEATURES

- For Indoor Wall Mount Applications
- Powder Coated 16 Gauge Cold Rolled Steel (Beige or Black)
- Accommodates (1) LGX Adapter Plate
- 12 Fiber Splice Holder Included
- Available with Optional DIN Rail Mount

The AFWMC-I provides protection for fiber optic terminations and splices in a compact design. The enclosure accommodates (1) LGX style adapter plate and can be configured to house up to (12) SC footprint adapters and 12 splices using the included splice holder. The AFWMC-I is available unloaded, with pigtails and adapters, or can be equipped with a pre-terminated stub cable per the customer's specifications. DIN rail mounting options also available.

### SPECIFICATIONS

Model	AFWMC-I
Dimensions	6" H X 6" W X 1.8" D
Entry Points	2
Material	16 Gauge Cold Rolled Steel
Splice Tray	None – 12 Fiber Self-Adhesive Splice Holder Included

### ACCESSORIES

SC Simplex SM Adapter, Blue	AFAD2F2F
SC/APC Simplex SM Adapter, Green	AFAD5F5F
LC Duplex SM Adapter, Blue	AFAD4F4F-DU-SC
LC Duplex MM Adapter, Aqua	AFAD4F4F-DU-10G-SC
LC/APC Duplex SM Adapter, Green	AFAD4F4F-DU-SC
SC Simplex MM Adapter, Beige	AFAD2F2F-MM
LC Duplex MM Adapter, Beige	AFAD4F4F-DU-MM-SC