

AFWMS-12x6-OSP

OSP Wall Mount FDP



*Shown Unloaded

FEATURES

- For Outdoor Wall or Pole Mount Applications
- Powder Coated 11 Gauge Aluminum (Beige)
- Accommodates up to 144 Ports SC or 288 Ports LC (As Patch Only)
- Accommodates up to (6) splice trays
- (4) 1-5/8" Diameter Cable Entry Points
- NEMA 4 Rated

The AFWMS-12x6-OSP provides NEMA 4 protection for fiber terminations and splices in the outside plant environment. The enclosure is equipped with (4) 1-5/8" ports for cable entry and accommodates (12) LGX 118 adapter plates and up to (6) splice trays. The enclosure is configured for wall mounting but may also be pole mounted using the optional pole mounting hardware. The AFWMS-12x6-OSP is available as a patch only, patch and splice, or can be equipped with a pre-terminated stub cable per the customer's specifications.

SPECIFICATIONS

Model	AFWMS-12x6-OSP
Dimensions	22"h X 17.1"w X 7.1"d
Material	11 Gauge Aluminum
Maximum Termination Capacity	(144) SC or (288) LC (Patch Only)
Splice tray Capacity When Equipped	144 Splices (Loose Tube)

ACCESSORIES

AFWMS-12X6-OSP Pole Mount Bracket	MIC10969
-----------------------------------	----------