

PRE-TERM CABLE ASSEMBLIES CONFIGURATOR

Part Number

FA _____ / _____ - _____

1 2 3 4 5 6 7 8 9 10

1 = Fiber Type

S = Singlemode
 M = Multimode

2 = # of Strands

004	048
006	060
012	072
018	096
024	144
036	288

3 = Cable Type

A = Indoor, Riser Rated
 B = Indoor, Plenum Rated
 C = Indoor/Outdoor, Riser Rated
 D = Indoor/Outdoor, Plenum Rated
 E = Outside Plant/Outdoor

4 = Side A

1 = ST	8 = MTRJ (M)
2 = SC	9 = MTRJ (F)
3 = FC	10 = Biconic
4 = LC	11 = D4
5 = SCAPC	12 = MTP (F)
6 = FCAPC	13 = MTP (M)
7 = Open	14 = LCAPC

5 = Side B

1 = ST	8 = MTRJ (M)
2 = SC	9 = MTRJ (F)
3 = FC	10 = Biconic
4 = LC	11 = D4
5 = SCAPC	12 = MTP (F)
6 = FCAPC	13 = MTP (M)
7 = Open	14 = LCAPC

6 = Breakout Length

1 = 12"
 2 = 18"
 3 = 24"
 4 = 36"
 5 = 48"
 6 = 60"
 7 = 72"

7 = Furcated Breakout

N = 900um Legs
 Y = 2mm Furcation

8 = Pulling Eye

N = None
 Y = Yes, One Side
 Y2 = Yes, Both Sides

9 = Length

XXXF = Feet
 XXXM = Meters

10 = Additional Specifications

10G = OM3 (50um)
 10G4 = OM4 (50um)
 BI - Bend Insensitive
 AR = Armored OSP
 AIA = Aluminum Interlocking Armor
 MAR = Micro-Armor Style
 LT = Loose Tube
 MD = Micro Distribution Style
 RIB = Ribbon Style
 SJSA = Single Jacket Single Armor
 DIE = Dielectric
 YL = Yellow 2mm Furcated Legs

Custom Breakout
 Lengths and
 Styles Available

Need assistance with selecting the correct pre-term cable assembly? Contact one of our experienced sales engineers to review your specific project needs.

Toll Free **866-518-5858**
 or email sales@amerifiber.com