

AFWNID-4-MINI FIBER OPTIC (NID)



*Shown Loaded As a 4 Port SCAPC

FEATURES

- For Wall Mount Applications
- Built In Splice Sleeve Holder
- Bulkhead Panel for 2 SC Duplex/LC Quad Adapters (SC Duplex Footprint)
- IP66 Rated, Weather Tight Grommets
- 2 Entry Ports
- Suitable for Outdoor or Indoor Cable
- Integrated Cable Management

The AFWNID-4-MINI provides IP-66 protection for fiber optic terminations and splices. The enclosure is equipped with 2 grommets for cable entry. The enclosure accommodates (2) SC duplex footprint adapters and features a molded splice sleeve holder and integrated slack management. The AFWNID-4-MINI is available unloaded or with pigtailed and adapters. Mounting hardware and splice sleeves included.

SPECIFICATIONS

Model	AFWNID-4-MINI
Dimensions	7" x 4.5" x 1.1" (17.8 x 11.4 x 2.8 cm)
Entry Points	2
Material	UV Resistant ABS
Suitable Cable Diameter	Up to 12 mm
Splice Sleeve Holder	Up to 8 Splices

ACCESSORIES

SC Duplex SM Adapter, Blue	AFAD2F2F-DU
SC/APC Duplex SM Adapter, Green	AFAD5F5F-DU
LC Quad SM Adapter, Blue	AFAD4F4F-QUA
LC Quad MM Adapter, Aqua	AFAD4F4F-QUA-10G
LC/APC Duplex SM Adapter, Green	AFAD14F14F-QUAD
SC Duplex MM Adapter, Beige	AFAD2F2F-MM-DU
LC Quad MM Adapter, Beige	AFAD4F4F-QUA-MM